



The CM series range of mesh graders are the ideal machines to calibrate potatoes, onions, table beets, garlic, etc.

They work by jumps of the mesh that obtains an optimum and careful calibration of the product.

Working ranges reaches up to 20 T/h, depending on the product, variety and it state.

They can be accompanied by the conveyors necessities to pick up the different measures after their calibration.

They are constructed entirely in stainless steel, have great resistance and are very low maintenance.

To complement this system, we offer a wide range of conveyors, vibrating multifunction hopes, hoppers, graders, washers, water recycling systems, etc.





## General features

- Perfect for potatoes, onions, table beets, garlic, etc.
- System of rise and fall of the mesh by eccentric axis.
- Each calibration body gives two calibers: pass-not pass.
- Mesh holes available between 20 and 120 mm.
- Robust structure in stainless steel.
- Protective bibs at the inlet to the machine.
- Speed control with mechanical variators (optional electronic) in motors.
- CE marked
- Optional: conveyor to pick up the product.

## Tecnical features

	Capacidad máxima (*)	Calibres	Medidas largo, ancho, alto	KW	Peso
<b>CMS820</b>	2-5 T/h	1 + resto	2.200 x 900 x 840 mm	1,1 KW	250 Kg
<b>CMS1220</b>	10-20 T/h	1 + resto	2.200 x 1.595 x 1.090 mm	1,1 KW	300 Kg
<b>CMS1520</b>	12,5-25 T/h	1 + resto	2.200 x 1.895 x 1.090 mm	1,1 KW	350 Kg
<b>CMD840</b>	2-5 T/h	2 + resto	3.960 x 900 x 840 mm	2,2 KW	500 Kg
<b>CMD1240</b>	10-20 T/h	2 + resto	3.960 x 1.595 x 1.090 mm	2,2 KW	600 Kg
<b>CMD1540</b>	12,5-25 T/h	2 + resto	3.960 x 1.895 x 1.090 mm	2,2 KW	700 Kg
<b>CMT855</b>	2-5 T/h	3 + resto	5.760 x 900 x 840 mm	3,3 KW	750 Kg
<b>CMT1255</b>	10-20 T/h	3 + resto	5.700 x 1.595 x 1.090 mm	3,3 KW	900 Kg
<b>CMT1555</b>	12,5-25 T/h	3 + resto	5.700 x 1.895 x 1.090 mm	3,3 KW	1050 Kg
<b>CMC875</b>	2-5 T/h	4 + resto	7.350 x 900 x 840 mm	4,4 KW	1000 Kg
<b>CMC1275</b>	10-20 T/h	4 + resto	7.350 x 1.595 x 1.090 mm	4,4 KW	1200 Kg
<b>CMC1575</b>	12,5-25 T/h	4 + resto	7.350 x 1.895 x 1.090 mm	4,4 KW	1400 Kg
<b>CMQ890</b>	2-5 T/h	5 + resto	9.150 x 900 x 840 mm	5,5 KW	1250 Kg
<b>CMQ1290</b>	10-20 T/h	5 + resto	9.150 x 1.595 x 1.090 mm	5,5 KW	1500 Kg
<b>CMQ1590</b>	12,5-25 T/h	5 + resto	9.150 x 1.895 x 1.090 mm	5,5 KW	1750 Kg

(\*) – Depending on type and variety of the product.

**Note:** other configuration and measures under request.