



The CM series range of mesh graders are the ideal machines to calibrate potatoes, onions, table beets, garlic, etc.

They work by jumps of the mesh that obtains an optimum and careful calibration of the product.

Working ranges reaches up to 20 T/h, depending on the product, variety and it state.

They can be accompanied by the conveyors necessities to pick up the different measures after their calibration.

They are constructed entirely in stainless steel, have great resistance and are very low maintenance.

To complement this system, we offer a wide range of conveyors, vibrating multifunction hopes, hoppers, graders, washers, water recycling systems, etc.





General features

- Perfect for potatoes, onions, table beets, garlic, etc.
- System of rise and fall of the mesh by eccentric axis.
- Each calibration body gives two calibers: pass-not pass.
- Mesh holes available between 20 and 120 mm.
- Robust structure in stainless steel.
- Protective bibs at the inlet to the machine.
- Speed control with mechanical variators (optional electronic) in motors.
- CE marked
- Optional: conveyor to pick up the product.

Tecnical features

	Capacidad máxima (*)	Calibres	Medidas largo, ancho, alto	KW	Peso
CMS820	2-5 T/h	1 + resto	2.200 x 900 x 840 mm	1,1 KW	250 Kg
CMS1220	10-20 T/h	1 + resto	2.200 x 1.595 x 1.090 mm	1,1 KW	300 Kg
CMS1520	12,5-25 T/h	1 + resto	2.200 x 1.895 x 1.090 mm	1,1 KW	350 Kg
CMD840	2-5 T/h	2 + resto	3.960 x 900 x 840 mm	2,2 KW	500 Kg
CMD1240	10-20 T/h	2 + resto	3.960 x 1.595 x 1.090 mm	2,2 KW	600 Kg
CMD1540	12,5-25 T/h	2 + resto	3.960 x 1.895 x 1.090 mm	2,2 KW	700 Kg
CMT855	2-5 T/h	3 + resto	5.760 x 900 x 840 mm	3,3 KW	750 Kg
CMT1255	10-20 T/h	3 + resto	5.700 x 1.595 x 1.090 mm	3,3 KW	900 Kg
CMT1555	12,5-25 T/h	3 + resto	5.700 x 1.895 x 1.090 mm	3,3 KW	1050 Kg
CMC875	2-5 T/h	4 + resto	7.350 x 900 x 840 mm	4,4 KW	1000 Kg
CMC1275	10-20 T/h	4 + resto	7.350 x 1.595 x 1.090 mm	4,4 KW	1200 Kg
CMC1575	12,5-25 T/h	4 + resto	7.350 x 1.895 x 1.090 mm	4,4 KW	1400 Kg
CMQ890	2-5 T/h	5 + resto	9.150 x 900 x 840 mm	5,5 KW	1250 Kg
CMQ1290	10-20 T/h	5 + resto	9.150 x 1.595 x 1.090 mm	5,5 KW	1500 Kg
CMQ1590	12,5-25 T/h	5 + resto	9.150 x 1.895 x 1.090 mm	5,5 KW	1750 Kg

(*) – Depending on type and variety of the product.

Note: other configuration and measures under request.