

Polisher LPR series





The new generation of LPR series polishers, with their revolutionary working system, are capable of polishing all type of vegetable and citrus, with a high performance and without causing any damage to the product.

The pendulum movement of the cradle provides a high efficiency of the system while that reduces of way remarkable the maintenance by replacement of brushes

The LPR420 model is also ideal for an improvement of polishing of determined sizes, allowing the presentation of the final product to the most demanding markets.

Our wide range of models allow us to offer the best system at an affordable cost which guarantees a rapid return of investment.

To complement this system, we offer a wide range of conveyors, vibrating multifunction hopes, hoppers, graders, washers, water recycling systems, etc.



MARTIN MAQ Autovçia A601 - Salida 91 40291 - Tabanera la Luenga - Segovia martinmaq@martinmaq.com www.martinmaq.com







Main features

- Unique "pendulum" action and brushes in "U" formation (patented).
- Compact desing.
- Design of drum for a processing continued.
- Brushes designed by Martin Maq.
- Adjustable brushing speed.
- Adjustable drum turning speed.
- Adjustable output gate to fit the required production.
- Shower/sprays circuits for washing/rinsing a product and cleaning the machine
- Built entirely in stainless steel.
- Full electric switchboard.
- Brushes can be changed without having to pull out the axel from the machine.
- Easy access to important areas for maintenance.
- Direct drive on models LPR830M and LPR1235M.
- CE marking.
- Options:
 - Water recovery system.
 - \circ Pneumatic lifting system.

Tecnical features

	Estimated capacity (*)	Estimated water consumption without recycling (*)	Estimated water consumption with recycling (*)	Size L, w, h	KW	Weight
LPR420	Potato: 4-6 T/h Carrot: 2-3,5 T/h	8 – 12 m³/h	1 m³/h	2.475 x 1.500 x 1.600mm	x 2,4 KW	870 Kg
LPR620	Potato: 6-8 T/h Carrot: 4-5 T/h	8 – 12 m³/h	1 m³/h	2.860 x 1.500 x 1.600mm	3,55 KW	950 Kg
LPR830M	Potato: 15-20 T/h Carrot: 9-12 T/h	10 – 15 m³/h	1,5 m³/h	3850x2000x 2100mm	15 KW	2100 Kg
LPR1235M	Potato: 25-30 T/h Carrot: 15-20 T/h	13 – 18 m³/h	2 m³/h	4.530 x 2.280 x 1.670mm	20,2 KW	2.700 Kg

(*) – Depending on type, variety and quality of the product.

MARTIN MAQ

INNOVATIVE ENGINEERING

Autovçia A601 - Salida 91 40291 - Tabanera la Luenga - Segovia martinmaq@martinmaq.com www.martinmaq.com